


M.2

hex 27 integrated



Socket device included in the delivery



0194

Diaphragm pressure switches up to 24 V with gold contacts

- Made of zinc-plated steel (CrVI-free)
- Socket device similar to DIN EN 175301 (DIN 43650)
- Changeover with gold contacts
- Overpressure safety up to 100 / 400 bar¹⁾
- Hysteresis adjustable at factory

P_{max} in bar	Adjustment range in bar	Tolerance at room temperature in bar	Male thread	Article number
---------------------	----------------------------	---	-------------	----------------

0194 Diaphragm pressure switches

P_{max} in bar	Adjustment range in bar	Tolerance at room temperature in bar	Male thread	Article number	
100 ¹⁾	0.3 - 1.5	± 0.2	G1/4	0194 - 457 03 - X - 003	
			M10x1 con.	0194 - 457 01 - X - 001	
			M12x1.5 cyl.	0194 - 457 02 - X - 002	
			NPT1/8	0194 - 457 04 - X - 318	
			NPT1/4	0194 - 457 09 - X - 314	
			7/16-20 UNF	0194 - 457 20 - X - 301	
			9/16-18 UNF	0194 - 457 21 - X - 302	
400 ¹⁾	1 - 10	± 0.5	G1/4	0194 - 458 03 - X - 042	
			M10x1 con.	0194 - 458 01 - X - 040	
			M12x1.5 cyl.	0194 - 458 02 - X - 041	
			NPT1/8	0194 - 458 04 - X - 343	
			NPT1/4	0194 - 458 09 - X - 340	
			7/16-20 UNF	0194 - 458 20 - X - 341	
				9/16-18 UNF	0194 - 458 21 - X - 342
	10 - 50	± 3.0	± 3.0	G1/4	0194 - 459 03 - X - 009
				M10x1 con.	0194 - 459 01 - X - 007
				M12x1.5 cyl.	0194 - 459 02 - X - 008
				NPT1/8	0194 - 459 04 - X - 320
				NPT1/4	0194 - 459 09 - X - 311
7/16-20 UNF				0194 - 459 20 - X - 305	
			9/16-18 UNF	0194 - 459 21 - X - 306	
10 - 100	± 3.0 - 5.0	± 3.0 - 5.0	G1/4	0194 - 461 03 - X - 012	
			M10x1 con.	0194 - 461 01 - X - 010	
			M12x1.5 cyl.	0194 - 461 02 - X - 011	
			NPT1/8	0194 - 461 04 - X - 321	
			NPT1/4	0194 - 461 09 - X - 312	
			7/16-20 UNF	0194 - 461 20 - X - 307	
			9/16-18 UNF	0194 - 461 21 - X - 308	

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
FFKM	Chemical acids, diluted alkalis, ketones, ester's, alcohols	6
HNBR ²⁾	Hydraulic/machine oil, ester-based bio-oils	9

Refer to page 33 for the temperature range and application thresholds of sealing materials.



Article number: **0194 - XXX XX - X - XXX**



¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.
²⁾ HNBR diaphragm not available for pressure ranges 0.3 - 1.5 bar.