




0132 / 0133 / 0134 / 0135 / 0136 / 0137

Diaphragm/piston pressure switches with integrated connector, maximum operating voltage up to 48 V




- Simple, quick and reliable electrical connection with easy-to-fit connectors
- Quick fitting with socket wrench (spanner)
- Changeover with silver contacts (gold contacts available as option)
- Hysteresis adjustable at factory
- Made of zinc-plated steel (CrVI-free, other housing materials available as option)

Model / type ▶




	0132 / 0133	0134 / 0135	0136 / 0137
			
	TE AMP Superseal 1.5® IP67	M12x1 EN61076-2-101-A Contact assignment DIN 60947-5-2 IP67	Deutsch DT04-3P® IP67, IP6K9K
Height without thread ▶	H ≈ 73 mm	H ≈ 65 mm	H ≈ 71 mm

Height without thread ▶

Contact assignments ▶

		
---	--	---

Circuit diagrams ▶

		
---	--	---

¹⁾ Blade of screwdriver max. 2 mm

Accessory ▶

Not included
in the delivery.

Please order separately.

Mating plug with 2 m cable

	TE AMP Superseal 1.5®	M12x1 DIN EN 61076-2-101-LF	Deutsch DT06-3S®
			
Cable cross-section / IP protection ▶	3 x 0,5 mm ² Radox cable / IP65	4 x 0,34 mm ² PUR cable / IP67	3 x 0,5 mm ² PUR cable / IP67
Article number ▶	1-1-32-653-158	1-1-00-653-162	1-1-36-653-160

Cable cross-section /
IP protection ▶

Article number ▶

0132 / 0133 / 0134 / 0135 / 0136 / 0137

Diaphragm/piston pressure switches with integrated connector, maximum operating voltage up to 48 V

M.2
hex 27 integrated



p_{max} in bar	Adjustment range in bar	Tolerance at room temperature in bar	Thread	Article number
---------------------	----------------------------	---	--------	----------------

0132 / 0134 / 0136 Diaphragm pressure switches

100 ¹⁾	0.3 - 1.5	± 0.2	G1/4	013X - 457 03 - X - 003
			M10x1 con.	013X - 457 01 - X - 001
			M12x1.5 cyl.	013X - 457 02 - X - 002
			NPT1/8	013X - 457 04 - X - 318
			NPT1/4	013X - 457 09 - X - 314
			7/16-20 UNF	013X - 457 20 - X - 301
			9/16-18 UNF	013X - 457 21 - X - 302
			G1/4	013X - 458 03 - X - 042
			M10x1 con.	013X - 458 01 - X - 040
			M12x1.5 cyl.	013X - 458 02 - X - 041
			NPT1/8	013X - 458 04 - X - 343
			NPT1/4	013X - 458 09 - X - 340
400 ¹⁾	1 - 10	± 0.5	7/16-20 UNF	013X - 458 20 - X - 341
			9/16-18 UNF	013X - 458 21 - X - 342
			G1/4	013X - 459 03 - X - 009
			M10x1 con.	013X - 459 01 - X - 007
			M12x1.5 cyl.	013X - 459 02 - X - 008
			NPT1/8	013X - 459 04 - X - 320
	10 - 50	± 3.0	NPT1/4	013X - 459 09 - X - 316
			7/16-20 UNF	013X - 459 20 - X - 305
			9/16-18 UNF	013X - 459 21 - X - 306
			G1/4	013X - 461 03 - X - 012
			M10x1 con.	013X - 461 01 - X - 010
			M12x1.5 cyl.	013X - 461 02 - X - 011
	10 - 100	± 3.0 - 5.0	NPT1/8	013X - 461 04 - X - 321
			NPT1/4	013X - 461 09 - X - 317
			7/16-20 UNF	013X - 461 20 - X - 307
			9/16-18 UNF	013X - 461 21 - X - 308

0133 / 0135 / 0137 Piston pressure switches

700 ¹⁾	50 - 200	5.0	G1/4	013X - 460 03 - X - 003
			M10x1 con.	013X - 460 01 - X - 001
			M12x1.5 cyl.	013X - 460 02 - X - 002
			NPT1/8	013X - 460 04 - X - 304
			NPT1/4	013X - 460 09 - X - 303
			7/16-20 UNF	013X - 460 20 - X - 301
			9/16-18 UNF	013X - 460 21 - X - 302

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
FFKM	Chemical acids, diluted alkalis, ketones, ester's, alcohols	6
HNBR ²⁾	Hydraulic/machine oil, ester-based bio-oils	9

Refer to page 33 for the temperature range and application thresholds of sealing materials.

Article number: **013 X - XXX XX - X - XXX**

¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.

²⁾ HNBR diaphragm not available for pressure ranges 0.3 - 1.5 bar.

